

OCN+ Server Display


Features

- Intel i5-10210U CPU
- DDR4 SODIMM x2
- LCD+HDMI dual display
- Full flat touch screen, front panel IP65 protection
- Low power fanless
- 9 ~ 36V wide voltage input



Specification

System		
Name	SRV_OCN+_DIS15 or SRV_OCN+_DIS19	
Processor	Intel i5-10210U CPU	
System memory	DDR4 SODIMM x2	
Network	2x 2.5 GbE RJ45 Intel i225V (4 x 2.5GbE RJ45 Intel i225V)	
I/O interface	2 x USB2.0, 4 x USB3.0 (Intel Core i5) 2 x DB-9 COM1 & COM2, RS-232/422/485 1 x Audio Line-out 1XAT/ATI DIP switch 1X HDMI 1 x Expansion 10: Integrated 4-way 3-wire COM, 10-way GPIO	
Storage	1 TB	
Support system	LINUX	
Structure		
Material	Aluminum	
Installation method	VESA 75/100 Panel Mount	
Size	376.13x285.34x68.90 mm	
Weight	TBD	
Use environment		
Work temperature	-20°C ~ 60 °C	
Storage temperature	-30°C ~ 70 °C	
Storage humidity	10~90% @30°C, no condensation	
Power supply		
Power input	DC 9 ~ 36V 4-pin Aerial insertion	
Display		
LCD	15.0" TFT-LCD or 19.0" TFT-LCD	
Resolution	1024 x 768	
Max color	16.7M	
Brightness	350 cd/m²	
Perspective (CR >= 10)	-85 ~ 85° (H), -85 ~ 85° (V)	
Backlight	LED	
Backlight life(hours)	30,000	
Touch screen		
Type	5-wire resistive	Projected Capacitor
Transmittance	78%	>85%
Service life	250a clicks 10 million times	>50 Million times



OCN+ Server Display

PC Dimensions • Unit: mm

